

	Approved For Release 2000/04/14 : CIA-RDP71B					ROUTING						
ORIG:	Approved For Release	2000/04/1	4 : CIA-F	RDP71B	026	3R00020030	DO	04-1	The state of the s			
UNIT:		000	5-(L) A		2		10					
EXT:			, , , , , , , , , , , , , , , , , , , 		3	+ marking order or any order or any order or any order	111					
DATE					 		113	***************************************	······································			
TO :					13+		13		******			
		Consiste a	n en	regalis in de	計		15					
FROM:					8		16					
				•	1				elaithal			
CONF	PAGE 2			4	or FO	DEFERRED		PRIORITY				
			***		8	ROUTINE		PERATIONAL	includes.			
INFO:			•					MMEDIATE				
				• • • •				1-116	1			
							1	13519				
							U	•				
TO	in	FG				CITE						

H. REPEAT (G)

IV. EQUIPMENT WILL BE OPERATED AS FOLLOWS:

A. PRIOR TO TAKE-OFF SYSTEM 12B-1 SWITCHED TO PWR "ON". MC RECORDER "ON", 13C TO "STDBY" AND "ON".

25X1D0f

- PRIOR TO REACHING PT (A) IFF WILL BE SWITCHED "OFF" AND REMAIN "OFF" FOR DURATION OF TEST.
- C. ON LEG ONE (PT A TO PT B) SYSTEM 12B-1 WILL BE "ON" AND 13C IN "STDBY".
- D. ON LEG TWO (PT B TO PT A) THE 13C WILL BE SWITCHED TO "RPT" MODE AND 12B-1 REMAIN "ON".
- E. ON LEG THREE (PT C TO PT D) THE 13C WILL BE SWITCHED TO "STDBY" AND 12B-1 TO "OFF".
- F. LEG FOUR (REPEAT E) THE 13C WILL BE TURNED TO "RPT" MODE AND 12B-1 WILL REMAIN OFF FOR REMAINDER OF TEST.
 - G. LEG FIVE (PT E TO PT F) THE 13C WILL BE TURNED TO "STDBY".
- H. LEG SIX (REPEAT G) THE 13C WILL BE SWITCHED TO "RPT" MODE.

			COORDINATING OFFICERS		
				COCUS I Control from majorphi	
EASING OFFICER				A made de la constante de la c	AUTHENTICATING OFFICER
Appro	SEELLECH	Refer	BY COURSE AND THE PASH OF	97E60263R00	8 250 300 664-4

RELEASING OFFICER

ORIG: Approved For Release 2000/04/14 : CIA-RDP71B00263R0002003000			
UNIT: [2]			
EXT:			
DATE:			
13			
TO :	and the same of th		
FROM: 15	- The same of the		
	INITALS		
CONF: PAGE THREE	PRIORITY		
ROUTINE C	PERATIONAL INFINA		
INFO:	IMAEDIATE		
	43519		
)3.1		
TO INFO CITE			

- I. LEG SEVEN (PT G TO PT H) THE 13C WILL BE SWITCHED TO "STDBY".
 - J. LEG EIGHT (REPEAT I) THE 13C WILL BE SWITCHED TO "RPT" MODE.
- V. TO ENSURE THAT HEADQUARTERS OBTAINS VALID TEST DATA IT IS REQUESTED THAT THE FOLLOWING GUIDELINES BE CAREFULLY FOLLOWED:

25X1A2q A. PILOT AND ESTABLISH A TIME REFERENCE.

25X1A2g B. PILOT WILL INFORM OF SYSTEM STATUS PRIOR TO POINT (A).

- 25X1A2g C. WILL PROVIDE PILOT WITH RANGE TO SITE AT MINUTE INTERVALS STARTING AT PT A. THIS IS TO BE DONE ON LEGS ONE AND TWO ONLY.
 - C. ON LEGS ONE AND TWO PILOT WILL ANNOTATE POSITION, LENGTH AND DESCRIPTION OF 12B-1 STROBE, (I.E., 12 O'CLOCK, 1 OR 2 SCOPE DIVISIONS, FEATHERED, DISAPPEARANCE, ETC.) BETWEEN EACH MINUTE INTERVAL. IT IS IMPERATIVE THAT THIS REPORTING BE AS ACCURATE AS POSSIBLE.

 25X1A2q
 - D. PILOT WILL KEEP POSTED ON SYSTEMS OPERATION

RELEASING OFFICER

engles ; Bachalid ben menanir Campudda con decuplentes

AUTHENTICATING OFFICER

	CLASSIFIED MESSAGE			POUTING						
ORIGÎ	Approved For Release 2000/04/14 : CIA-RDP	71B0	02	€ 3R0002003	0000	04-1	and the second s			
UNIT :			2		10	and distribution of a section of				
EXT:			3		111	All halps are the party of the Party	i an d an plant for an a side and a			
DATE:			4		12		-			
		-	5		13		/ 			
TO :	in and the state of the state o	,	6		14					
			7		15					
from:		.	8		196					
CONF:			Roman	DEFERRED	P	RIORITY	initial8			
INPO:	PAGE FOUR		ROZZ	ROUTIME		erational Hediate	MITTELS			
					- 12	135	19			
					<i>y</i>					
70	(ALEX)			CITE						

DURING TEST.

VI, THE INTERCOM WILL BE SWITCHED TO "RECORD ALL" POSITION IN ORDER TO RECORD ALL GROUND/AIR COMMO AND PILOT'S ANNOTATIONS.

VII. DATA REQUIRED:

- A. MC RECORDER TAPE WITH FOLLOWING RECORDED DATA
 - 1. TIME CODE SIGNAL
 - 2. 12B-1
 - 3. 13C
 - 4. AIR/GROUND COMMO
- B. RECORDING OF PILOT BRIEFING AND DEBRIEFING
- C. GENERAL COMMENTS.

RND OF MESSAGE

25X1A9a

COORDINATING OFFICERS

D/M/OSA

RELEASING OFFICER

AUTHENTICATING OFFICER

DEPONDED AUTHENTICATING OFFICER

Approved Political Approved Poli